

width: up to 21 m
height: up to 2,50 m



SLIDING GATE INCLINED

Our individual solutions are tailored to suit the environment for both technical function and aesthetics..

Challenging incline installations are no problem. We adapt our design to the given situations, including the correct drive system complete with failsafe protection.

RADIAL DAMPER

All sliding gates which can be adapted to the incline area are equipped with a radial damper. This prevents the gate to move in unintended direction when the drive is unlocked and ensures a smooth controlled movement.



The gear is made of stainless steel and the freewheel is sealed against dirt and water.



15 m inclined sliding gate, Perforated, Automation Inline 250



6 m inclined sliding gate, Plain sheet, Automation Inline 250



CONVINCING ARGUMENTS

Automation	24V up 230V INLINE is installed in the post, not-visibly from the outside
Control system	Electronic control according to the latest standards
Closure and accessories	Locinox lock including spring-loaded strike plate, E-preparation, deadman or complete plug & play automation
corrosion protection	Thanks to its own powder coating: easy-care, scratch-resistant, weather-resistant and provides a beautiful surface for many years
Individualization	Spike bar, different fillings, etc.
Colors	RAL standard colors, special colors on request
Gate speed approx.	ca. 0,2 m/s, higher speeds on request
Incline	up to 25%
Gate width	up to 21 m



INLINE DRIVE SYSTEM INNOVATIVE AND ELEGANT

The BALU Inline drive convinces with its high-quality workmanship and special design. The design of the drive column is very impressive offering stability and protection of the drive and all control components by locating them within the column and away from potential vandalism and effects of weather. An integrated flashing LED lamp has also been installed on the column.



For more information visit us: www.b-alu.at